

CHAIN LINK FENCE

— BEST PARTNER OF MESH

Material:

- Stainless steel wire
- Black iron wire
- Electro galvanized iron wire
- Hot dipped galvanized wire
- Green/Black PVC coated iron wire

YISIZHE Chain link fence can meet the following standard:

American Standard: ASTM F567-14a, A392, A491, A817, A824, F552, F567

British Standard: BSEN1722-1

Australian Standard: AS1725.1-2010

For wide width, like 3.6m, 4.0m etc, basically used for tennis court. While the width usually less than 1.8m in Oceania countries. And the edge they require mostly be knuckled on both side.



Material	Stainless Steel wire/Black wire/ Galvanized wire/Hot dipped galvanized wire				PVC coated +Black wire/Electro galvanized wire/Hot dipped galvanized wire		
Mesh	Wire BWG	Wire Dia (mm)	Weight kg/m ²	Roll Dia 4"x50" (mm)	Wire Dia before/after	Weight kg/m ²	Roi Dia 4"x50" (mm)
3/8"(10mm)	13	2.4	7.1	280	2.6/3.2	3.7	280
	14	2.1	5.4	250	2.0/2.6	2.3	240
	16	1.6	2.9	230	1.4/2.0	1.2	220
	18	1.2	1.6	220	1.0/1.6	0.7	200
5/8"(16mm)	12	2.8	5.9	280	2.6/3.2	3.7	280
	14	2.1	3.3	250	2.0/2.6	2.3	240
	15	1.8	2.4	230	1.4/2.0	1.2	220
	17	1.4	1.3	220	1.0/1.6	0.7	200
1"(25mm)	12	2.8	3.87	220	2.6/3.2	3.7	280
	13	2.4	2.9	220	2.0/2.6	2.3	240
	14	2.1	2.3	180	1.4/2.0	1.2	220
	16	1.6	1.34	160	1.0/1.6	0.7	200
1.5"(40mm)	10	3.4	3.7	280	3.4/4.0	3.9	290
	11	3	3	250	2.6/3.2	2.4	280
	12	2.8	2.4	230	2.0/2.6	1.4	240
	14	2.1	1.4	220	1.4/2.0	0.8	220
2"(50mm)	8	4.2	3.7	280	3.4/4.0	3.2	280
	10	3.4	3	250	2.6/3.2	1.9	250
	12	2.8	2.4	230	2.0/2.6	1.2	230
	14	2.1	1.4	220	1.4/2.0	0.6	220
2.25"(56mm)	8	4.2	3.9	280	3.4/4.0	2.8	280
	10	3.4	2.6	250	2.6/3.2	1.7	250
	12	2.8	1.7	230	2.0/2.6	1	230
	14	2.1	1	220	1.4/2.0	0.55	220
2.4"(60mm)	8	4.2	3.7	290	3.4/4.0	2.6	290
	10	3.4	2.5	280	2.6/3.2	1.6	280
	12	2.8	1.63	250	2.0/2.6	1	250
	14	2.1	1	220	1.4/2.0	0.48	230
2.5"(64mm)	8	4.2	3.5	290	3.4/4.0	2.5	300
	10	3.4	2.3	280	2.6/3.2	1.5	280
	12	2.8	1.6	250	2.0/2.6	0.9	250
	14	2.1	0.9	220	/	/	/
2.5"(64mm) 3"(76mm)	8	4.2	3	300	4.4/5.0	3.4	300
	10	3.4	2	290	3.4/4.0	2.1	290
	12	2.8	1.3	280	2.6/3.2	1.3	250
	14	2.1	0.8	250	/	/	/
3"(76mm)	8	4.2	2.2	300	4.4/5.0	3.4	300
	10	3.4	1.3	290	3.4/4.0	2.1	290
	12	2.8	0.9	280	2.6/3.2	1.3	250
	14	2.1	0.6	250	/	/	/

Technical Notes:

Min wire diameter: 0.8mm

Min Opening: 3/8"


Weight(kg): Wire diameter(mm)xWire diameter(mm)x0.6425+aperture(cm)x2=kg/m²

THE EDGE OF CHAIN LINK FENCE

— BEST PARTNER OF MESH

Barb-Barb

Top



Bottom

Knuckle-Barb


Top



Bottom

Knuckle-Knuckle

Top



Bottom

