

RAZOR WIRE


— BEST PARTNER OF MESH

Material:

- Electro galvanized iron
- Electro galvanized steel
- Hot-dipped galvanized iron
- Hot-dipped galvanized steel
- Stainless steel
- Black iron wire and PVC coated in orange, green, yellow and other colors
- Electro galvanized wire and PVC coated in orange, green, yellow and other colors
- Hot-dipped galvanized wire and PVC coated in orange, green, yellow and other colors



RAZOR WIRE SPECIFICATION

CONCERTINA RAZOR WIRE							
Reference Number	Blade Style	Thickness (mm)	Wire Dia (mm)	Barb Length (mm)	Barb Width (mm)	Barb spacing (mm)	Weight (g)/m
BTO-10		0.5±0.05	2.5±0.1	10±1	13±1	26±1	77g/m
BTO-12		0.5±0.05	2.5±0.1	12±1	15±1	26±1	79g/m
BTO-18		0.5±0.05	2.5±0.1	18±1	15±1	33±1	87g/m
BTO-22		0.5±0.05	2.5±0.1	22±1	15±1	34±1	91g/m
BTO-28		0.5±0.05	2.5±0.1	28±1	15±1	45±1	103g/m
BTO-30		0.5±0.05	2.5±0.1	30±1	18±1	45±1	95g/m
CBT-60		0.6±0.05	2.5±0.1	60±2	32±1	100±2	106g/m
CBT-65		0.6±0.05	2.5±0.1	65±2	21±1	100±2	115g/m

BARBED TAPE WIRE SPECIFICATION				
Outside Diameter	No. of Loops	Standard Length per Coil	Type	Notes
450mm	33	7-8M	CBT-60.65	Singlecoil
500mm	56	12-13M	CBT-60.65	Singlecoil
700mm	56	13-14M	CBT-60.65	Singlecoil
960mm	56	14-15M	CBT-60.65	Singlecoil
450mm	56	8-9M(3CLIPS)	BTO-10.12.18.22.28.30	Crosstype
500mm	56	9-10M(3CLIPS)	BTO-10.12.18.22.28.30	Crosstype
600mm	56	10-11M(3CLIPS)	BTO-10.12.18.22.28.30	Crosstype
600mm	56	8-10M(5CLIPS)	BTO-10.12.18.22.28.30	Crosstype
700mm	56	10-12M(5CLIPS)	BTO-10.12.18.22.28.30	Crosstype
800mm	56	11-13M(5CLIPS)	BTO-10.12.18.22.28.30	Crosstype
900mm	56	12-14M(5CLIPS)	BTO-10.12.18.22.28.30	Crosstype
960mm	56	13-15M(5CLIPS)	BTO-10.12.18.22.28.30	Crosstype
980mm	56	14-16M(5CLIPS)	BTO-10.12.18.22.28.30	Crosstype

FLAT-WARP RAZOR WIRE		
High	Standard cover length	Weight
500mm(20inch)	15M(50ft)	9.5kg(21lbs)
700mm(28inch)	15M(50ft)	13.0kg(29lbs)
900mm(36inch)	15M(50ft)	14.5kg(32lbs)

WELDED RAZOR WIRE FENCE				
Hole Size	Hole Style	Width	Length	Blade style
75mm x 150mm	Square or Diamond	0.3m-5.8m	1.0m-11.8m	BTO-10.12.18.22.28.30 CBT-60.65
100mm x 100mm	Square or Diamond	0.3m-5.8m	1.0m-11.8m	BTO-10.12.18.22.28.30 CBT-60.65
100mm x 150mm	Square or Diamond	0.3m-5.8m	1.0m-11.8m	BTO-10.12.18.22.28.30 CBT-60.65
100mm x 200mm	Square or Diamond	0.3m-5.8m	1.0m-11.8m	BTO-10.12.18.22.28.30 CBT-60.65
150mm x 300mm	Square or Diamond	0.3m-5.8m	1.0m-11.8m	BTO-10.12.18.22.28.30 CBT-60.65

APPLICATIONS

